
Product Description

This standard tack application tape is designed to suit most signmaking applications. It allows easy unwind off the roll, and clean tear. The high quality paper demonstrates excellent layflat properties with low elongation. It is easy to remove without residue and is suitable for wet application.

Its natural rubber adhesive makes it suitable for the transfer of both matt and gloss surfaces and it is excellent for small letters and logos.

Applications

Transfer of computer cut pvc films with gloss or matt surfaces.

Excellent for transferring small letters and logos.

Suitable for wet application.

Specifications

Adhesive:	Natural Rubber
Tack:	Standard
Paper:	White special

Specifications

Tape thickness:	110 mic
Adhesion to steel:	1.95 N/cm
Tear Strength:	38.0 N/cm
Elongation:	3.20%

Warranty: Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics.

Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.