

Metamark MD-PU

Polyester for 'Pop Up' Displays – 310 micron

METAMARK
The Materials Company

Product Description

Metamark MD-PU is a 310 micron, semi rigid, 'Lightstop' polyester, for use on solvent inkjet printers. It has coated matt white printable surface that is scratch resistant, and an antistatic white film on the reverse. Between these two films is a total block membrane, providing full opacity. For use with modular 'Pop Up' display systems, for use in exhibitions and for POS.

Material Handling

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static. Always perform a test print first.

Printing Guidelines

- Suitable for use on Solvent and Eco Solvent inkjet printers.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- Do not stack prints until fully cured. Avoid use of take up roller to prevent blocking.

Overlaminating

- The product is designed to be used with MetaGuard 403 overlaminate to provide the desired finish and abrasion resistance.
- Allow the inks to cure before overlaminating, this is nominally 24-48 hours but dependant on the inks.
- Do not roll tighter than 200mm diameter once laminated

Film Specifications

Type	Laminated, white coated polyester print surface, total block membrane, white anti static reverse.
Thickness	310 micron
Service temperature	10°C to 30°C

Finishes

Finish Available	MD-PU	White 'Pop Up' Polyester
------------------	-------	--------------------------

Roll Presentation

Roll sizes	914mm x 20m 1270mm x 20m
Presentation	Face film outwards

Durability

Shelf Life	2 years
Durability	Indoor use, waterproof.
Fire Rating	Combustible but not readily ignited.

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark DigitalVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

● Moorfield Road Styfield Industrial Estate Guildford GU1 1RU Tel +44 (0)1483 571111 Fax +44 (0)1483 570540
● Lunsdale New Quay Road Lancaster LA1 5QP Tel +44 (0)1524 387140 Fax +44 (0)1524 387147

www.metamark.co.uk
sales@metamark.co.uk