

# Metamark MD-RU160

Polyester for 'Roll Up' Banner Stands - 160 micron

**METAMARK**  
The Materials Company

## Product Description

Metamark MD-RU160 has been developed for use with 'Roll Up' banner stand display systems, for use on solvent inkjet printers. It has a crisp, matt white, anti reflective surface, and an anti static reverse surface, and blockout membrane giving maximum opacity and brilliant colour reproduction. Typical Applications include retractable roller banner stands, or static banner display systems, for use in exhibitions and retail displays.

## Material Handling

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.

## Printing Guidelines

- Suitable for use on Solvent and Eco Solvent inkjet printers. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from [www.metamark.co.uk](http://www.metamark.co.uk).
- Do not stack prints until fully cured. If a take up roller is used then a silicon liner may be interleaved to prevent blocking.

## Overlaminating

- The product is designed to be used with MetaGuard 302 overlaminate.
- Allow the inks to cure before overlaminating, this is nominally 24-48 hours but dependant on the inks.

## Film Specifications

Type	Polyester, grey 'lightstop' anti static backing
Thickness	160 micron
Service temperature	10°C to 30°C

## Finishes

Finish Available	MD-RU160	Matt white
------------------	----------	------------

## Roll Presentation

Roll sizes	914mm x 30m 1270mm x 30m
Presentation	Face film outwards

## Durability

Shelf Life	2 years
Durability	Indoor use, waterproof.
Fire Rating	Combustible but not readily ignited.

**Warranty:** Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Digital/Vinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

● Moorfield Road Styfield Industrial Estate Guildford GU1 1RU Tel +44 (0)1483 571111 Fax +44 (0)1483 570540  
● Luneside New Quay Road Lancaster LA1 5QP Tel +44 (0)1524 387140 Fax +44 (0)1524 387147

[www.metamark.co.uk](http://www.metamark.co.uk)  
[sales@metamark.co.uk](mailto:sales@metamark.co.uk)