

Product Description

Metamark Digital Static Cling is a 170 micron self-cling film available in white or clear. It can be applied to glass or metal and typically used to produce labels and promotional window decals. Once printed and contour cut, the printed surface can be applied to the glass and backing then removed. The white film provides opacity for solvent inks which are generally translucent.

Typical Applications

It can be applied to glass or metal and typically used to produce labels and promotional window decals.

Printing and Processing

Solvents from the printing process may initially cause the vinyl to soften and may initially reduce the strength of the adhesive, so after printing, leave 24 hours before applying the material and for the adhesive to regain full strength. To achieve the highest possible print quality please ensure that the correct profile is used. Ensure that the material has reached room temperature and a relative humidity of 50% before printing. Do not handle the face film directly and ensure it is free from dust and static. For a comprehensive list of printers compatible with MD-SC Digital Vinyl refer to the website.

Face Film

Face Film: 170 micron PVC

Adhesion

Adhesive: None
 Service Temperature: -20°C (-5°F) to 50°C (122°F)
 Application temperature: +10°C (+50°F) Min
 Adhesion: Both sides adhere securely on clean glass

Release Liner

Guage: 140gsm
 Type: Kraft

Finishes

Finishes Available: MD-SC-100 White Gloss
 MD-SC-105 Clear Gloss

Roll Presentation

Roll sizes: 760 x 25m
 1370mm x 25m
 Presentation: Face film outwards, on a 76mm core.

Durability

Shelf Life: 1 year
 External weathering: 2 Years Exterior, 5 Years Interior
 This refers to the unprinted vinyl when installed. Refer to ink manufacturer for durability of the finished product.

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark digitalvinyl will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark digitalvinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair.

Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.