

## Product Description

Metamark 'WallTex' is a low tack self-adhesive Polyester fabric, offering a clean, easy to apply alternative to traditional wall coverings. The fabric with its lightly textured weave is PVC free, and ideal for visual merchandising, exhibition and home décor applications. The repositionable adhesive is removable in the short term on sealed surfaces, allowing clean easy to replace wall décor coverings. It produces outstanding print results on Solvent, Eco Solvent, Latex and UV printers. Environmentally safe and bio-degradable over time, MD-TX2 is both PVC free and non-toxic

## Material Handling

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.

## Printing Guidelines

- Suitable for use on Solvent, Eco Solvent, Latex and UV printers. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from [www.metamark.co.uk](http://www.metamark.co.uk).
- Allow 24 hours after printing for the ink to gain abrasion resistance. Avoid use of take up roller and do not stack prints until fully cured.
- The durability of the finished print is dependent on the inks and printer. Check suitability before use.
- When printing each panel, the least colour variation will be achieved by alternating the orientation of each print. This will eliminate variance in colour across the printer width.

## Application

- The product will apply to emulsion painted walls, but to allow repositioning when applying, the paint must be sealed with primer and allowed to completely dry first. Unsealed emulsion paint will contaminate the adhesive and reduce tack when re applying.
- The surface must be non-porous, clean and dry, and free from condensation.
- Apply to smooth and flat surfaces; adhesion will be reduced on textured surfaces.
- Prior to application, clean the surface with a sponge and warm water and then allow to completely dry.
- Recommended application temperature > 15°C.
- Due to the variability of wall finishes and if there is any doubt, affix a trial sample to the wall for 24 hours to check adhesion.
- No liability is given for damage to painted surfaces as the bond between the paint and the wall is out of our control.
- Please refer to our Application Guidelines Bulletin [DécorMark Application Guide](#)

## Fabric Specifications

Fabric	100% surface coated polyester (PES)
Finish	Soft Sheen
Weight	110gsm
Denier	150Dx150D
Thickness	280 mic
Opacity	95%

## Adhesive

Type	Acrylic Solvent – Low tack Repositionable and Removable
------	--

## Liner

Release Liner	90gsm
---------------	-------

## Finishes

Finishes Available	MD-TX2 White
--------------------	--------------

## Roll presentation

Roll sizes	760mm x 30m 1370mm x 30m 1520mm x 30m
------------	---

## Durability

Shelf Life	Long term.
Fire Rating	M1
External weathering	Long term indoor, water resistant
Regulations	REACH compliant

**Warranty:** Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark DigitalVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

## Metamark (UK) Limited

- Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147
- Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540

[sales@metamark.co.uk](mailto:sales@metamark.co.uk)  
[www.metamark.co.uk](http://www.metamark.co.uk)