



M-PPF® Aftercare and Removal

Overview

Metamark M-PPF® is a range of professional paint protection films.

Following the correct aftercare and handling guidelines is important to ensure long-term, trouble-free protection of the vehicle, and performance of the films.

For more information visit www.metamark.co.uk/m-ppf or www.m-ppf.com









Cleaning

- ✓ Hand wash only, with a pH neutral shampoo.
- Do not pressure wash. Do not put through automated car washes, as may risk damage to the film.
- Remove stains as soon as possible. Use isopropyl alcohol to remove stubborn stains. Avoid cleaning the film in direct sunlight or in high temperatures.
- Dirt, debris, bird droppings and stains left on the film may discolour the film if not removed immediately, which may be more noticeable on light coloured cars.
- Do not use chemical cleaners on the film.

Scratch Removal

- Metamark M-PPF® films are self-healing. Light scratches will heal under warm conditions, or by use of hot water, or gently warming the film.
- Deep scratches cannot be healed when they have penetrated the top coated layer.

Use of Waxes

- ✓ Test all waxes or after-market sealants as not all products are compatible with top coated M-PPF® films.
- The hydrophobic top coat may interfere with the application of waxes or other coatings.
- ✓ Use of a professional detailer can enhance the finish.

Removal

- ✓ M-PPF® films will remove cleanly.
- Gently warm the film to make removal easier.
- Any adhesive residue can be removed with Metamark Adhesive Remover.
- ✓ Dispose of responsibly. The product is non-recyclable.

The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

