Metamark MD3-R

Removable Grade Digital Vinyl



Product Description

Metamark MD3-R is a removable intermediate grade calendered self-adhesive vinyl that provides excellent print performance on printers using solvent inks. It is ideal for temporary vehicle graphics, promotions and advertising. It is suitable for application to high energy surfaces such as steel and glass. Can be removed cleanly for up to 6 months after application

Features & Benefits

- Removable clear digital print media .
- For window graphics, retail, promotional and décor.
- Matched MetaGuard MG-300 Overlaminates
- Up to 1 year durability and MetaSure Warranty.
- For Solvent, Eco Solvent, Latex and UV printing.

Face Film		Finishes		
Face Film Gauge (ISO 2286-3) Fensile Strength	Calendered PVC 70 micron nominal 50N/25mm MD / 48N/25mm TD nom.	Finishes Available	MD3-R-200 MD3-R-301M	White Gloss White Matt
Elongation at break	180% MD nominal	Roll Presentation		
Adhesive		Roll Widths Roll Lengths	1.37m / 1.60m 50m	
Type Adhesion to glass 20 mins	Removable clear solvent-free acrylic 5N/25mm nominal	Durability	5011	
Adhesion to glass 24 hour Application temperature Service temperature	8N/25mm nominal +10°C to +50°C -30°C to +100°C	Shelf Life External weathering	1 years. (10-20°C and 50% R.H). 1 years (Unprinted) Clean removable upto 6 months. Northern European Metamark International durability guide	
Release Liner		Fire Rating	Class B - BS EN 13501-1:2007	
Print Weight Type	'Metamark Digital Vinyl' blue print 140 gsm nominal Layflat kraft with PE coating	Chemical Resistance	Unprinted film resistant to mild acids, aliphatic solvents, salt and alkali, diesel gasoline, paraffin, hydraulic oil, antifreeze.	
		Regulations	REACH and RoHS	Compliant.
Printing and Handling		Application		
 Always perform a test print first. Ensure that the correct profiles and heater settings are used. Refer to www.metamark.co.uk. Ensure that the material has reached room temperature and a 		 Allow a minimum of 24-48 hours for the solvents to dry off before application of the overlaminate, or to the substrate, depending on the print and drying conditions this can often be in excess of 48 		
Provide that the material has reached room temperature and a relative humidity of 50% before printing.Do not handle the face film, ensure free from dust and static.		 The user should determine suitability of substrate. 		
 The matched laminate for MD3-R is MetaGuard MG-300 Series 		Suitable for dry application		

- The matched laminate for MD3-R is MetaGuard MG-300 Series.
- Suitable for dry application.

MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Media and Overlaminates will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Media and Overlaminates becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited