Metamark MD-FL550

550gsm Premium FR Latex Banner



Product Description

Metamark MD-FL550 is a 550gsm high quality, coated PVC banner with a matt finish. It is suitable for use on Latex printers and is fire rated to B1. The product is suitable for medium to heavyweight banner applications, has high tensile strength and is resistant to cracking at low temperatures. It should be printed on the smooth side, and is not supplied reverse wound.

Material Handling

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.

Printing Guidelines

- Suitable for use on Solvent, Eco Solvent, Latex and UV inkjet printers. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- The product is reverse wound, so load material accordingly.
- The weight of the banner may necessitate some slack on the unwind.
- The product is designed to be used without an overlaminate. If a liquid laminate is used it is the responsibility of the user to test.
- The durability of the finished print is dependent on the inks and printer.

Fabric Specifications		Finishes	
Weight	550gsm	Finish Available	MD-FL550 Matt White Banner
Type Basic Fabric	Reinforce coated PVC PES. DIN ISO 2076	Durability	
Type of coating	PVC	Durability	
Tensile Strength	2500/ 2500 N/5cm (Warp / Weft)	Shelf I ife	2 years
Tear Strength	250/250 N (Warp / Weft)	Fire Rating	Fire rated to B1, DIN 4102 B1, M2,
Yarn	1100 dtex		NFPA - 701
Surface treatment	Acrylic lacquer	External weathering	3 years unprinted. This refers to the unprinted vinyl when installed. Refer to
Roll Presentation			ink manufacturer for durability of the
			finished product.
Roll sizes	760mm x 30m 1370mm x 30m 1600mm x 30m	Regulations	REACH compliant
Presentation	Face film inwards (reverse wound)		

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark DigitalVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.