Metamark MD-W300

DécorMark Pre-Pasted WallPaper



Product Description

For permanent wall coverings with a traditional construction, Metamark W300, with its non-woven paper construction gives minimal shrinkage, allowing invisible joints to be spliced in. With its pre-pasted construction, the water activated backing offers a clean easy handling solution where pastable wall coverings is the choice. The product has a smooth satin finish and a natural paper feel. It requires no lamination and is water resistant, PVC-free and FSC® certified. It is fire retardant to Class C, and printable with Solvent, Eco Solvent, Latex and UV printers.

Material Handling

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.
- To maintain the high quality of this wallpaper, it should be stored and converted in a climate of 30 65 % relative humidity and at a temperature of 10 30 °C (50 86 °F).

Printing Guidelines

- Suitable for use on Solvent, Eco Solvent, Latex and UV printers. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- Allow 24 hours after printing for the ink to gain abrasion resistance.
- When printing each panel, the least colour variation will be achieved by alternating the orientation of each print. This will eliminate variance in colour across the printer width.

Application

- Please refer to our Application Guidelines Bulletin DécorMark Application Guide
- Due to the variability of walls it is vital to assess the suitability, and surface preparation needed. It is suitable for smooth walls.
- No liability is given for damage to painted surfaces as the bond between the paint and the wall is out of our control.

Face Film			Roll Presentation	
Fabric Finish Weight (total)	Non-woven paper Satin 225gsm		Roll sizes	1067mm x 50m 1370mm x 50m
Thickness (total)	330 mic		Durability	
Opacity	91%		Shelf Life	Long term
Adhesive			External weathering	Long term indoor, water resistant
Туре	Permanent waterbased paste		Fire Rating Regulations	D-s1,d0 in accordance with EN 13501-1 : 2007 REACH compliant
Finishes			· ·	·
Finishes Available	MD-W300	Satin		

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark DigitalVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.