# **Metamark Carbon Fibre Effect**

# Calendered Vinyl with MetaScape® Adhesive System



### **Product Description**

For faster, trouble-free applications MMA-CF3 offers ease of application by providing air with an exit route from under the graphic. MMA-CF3 is a calendered PVC giving a realistic simulation of Carbon Fibre. It may be used on flat or simple curves so is ideal for large flat vehicle panels, such as bonnets and roofs. The 150 micron film has a textured, embossed 3D finish. It is durable for up to 5 years exterior use.

#### **Features & Benefits**

- Dry application only.
- Suitable for vehicle applications onto flat or simple curves.
- PVC, Phthalate and Chlorine Free.
- Textured embossed 3D finish.

Face Film		Finishes			
Face Film	Calendered Vinyl	Finishes Available	MMA-CF3	Carbon Fibre Effect	
Gauge	150 micron nominal		Durability		
Adhesive		Shelf Life	1 year. (10-20°C and 50% R.H).		
Туре	MetaScape® permanent solvent-based acrylic with air channels.	External weathering	5 years for in vertical exposure under northern European conditions.		
Adhesion to glass 20 mins Adhesion to glass 24 hour	15N/25mm nominal 20N/25mm nominal	Fire Rating	Self-extinguishing. The fire rating is a function of the substrate. Resistant to mineral oils, fats and fuels, aliphatic solvents, mild acids, salt and alkali for e.g. diesel oil, gasoline,		
Application temperature Service temperature	+10°C to +50°C -30°C to +110°C	Chemical Resistance			
Release Liner			•	g. diesei oii, gasoiine, ilic oil, antifreeze, soap	
Print	MetaScape print		suds etc.	me on, artifreeze, soup	
Weight	140 gsm nominal	Regulations	REACH & RoHS	compliant	
Туре	Layflat kraft paper with PE coating				

## **Application**

- Ideal for use on external applications including vehicle graphics onto smooth or flat panels as well as exterior sign applications.
- Suitable for plotter use, also for vinyl lettering.
- Apply unstressed, in particular to curves and recesses. It is not suitable for application over rivets or complex recesses.
- Suitable for dry application only.
- Due to the embossing of the film, it is more sensitive to tearing so care is needed when handling.
- The user should determine suitability of substrate.





# MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics. Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

## **Metamark (UK) Limited**