

# R Tape 4050 Conform

Low Tack Paper Application Tape



## Product Description

This low tack application tape is suitable for protective applications or transfer of certain low lift graphics. The paper is a standard weight saturated type designed specifically for pre space transfer applications in addition to metal protection. The adhesive is a natural rubber designed to achieve transfer of die cuts or pre spacing.

The Conform series is formulated with R Tapes advanced technology in release liner adhesion, resisting tunnelling and edge curling, even on rolled or stacked graphics. Conform series superior performance in lay flat and conformability presents neat, professional image and provides trouble free production, application, handling and storage.

## Features

- Covering for polished and non polished surfaces
- Covering for dull and embossed finishes.
- An all around transfer and pre spaced product
- Do not use for outdoor application

## Application

- Apply firm pressure with a squeegee.
- Graphics are best removed with the application tape facing downwards and lifting the release liner upwards.
- If the tape becomes wet, remove immediately after application while still wet, to prevent leaving residue on the vinyl.

## Storage

- Store in a cool, dry place. The paper and rubber based adhesive absorb moisture over time which will cause it to 'block' onto the roll if not stored correctly. This can also be prevented by storing in the polythene bag. Do not leave exposed in cold or damp conditions for any period of time. Do not get wet. Store on end.

| Type      |                | Specifications     |                    |
|-----------|----------------|--------------------|--------------------|
| Adhesive: | Natural rubber | Tape thickness:    | 4.5 mils           |
| Tack:     | Low            | Adhesion to steel: | 10-12 oz/ in width |
| Paper:    | Special white  | Tensile:           | 17 lb/in           |
|           |                | Elongation:        | 3-4%               |
|           |                | Tear resistance:   | 50grms             |

**Warranty:** Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

## Metamark (UK) Limited

○ Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147

○ Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540

[sales@metamark.co.uk](mailto:sales@metamark.co.uk)

[www.metamark.co.uk](http://www.metamark.co.uk)