# Metamark MD-AC370

# Art Canvas - 370gsm Satin Finish



## **Product Description**

Metamark MD-AC370 is a premium grade satin finish art canvas for tensioned fine art prints. It has a special acrylic coating offering a bright white finish, and giving vibrant colour brilliance with photo realistic definition. The lighter weight allows finer finishing of the framed print. It has an excellent drying time, crack resistance and is water fast. Suitable for fine art prints, stretched over a frame. For other applications the customer should be aware that the product will shrink as a result of the printing process. Shrinkage is minimal.

#### **Features**

- Suitable for fine art prints, stretched over a frame.
- Vibrant colour brilliance with photo realistic definition.
- PVC, Phthalate and Chlorine Free.
- Premium grade satin finish art canvas.

Fabric Specifications			
Weight Thickness Canvas Structure Type of Coating Fabric Blend Print Surface	1:1 Satin Finish 65% Polyester /	420 micron nominal 1:1	
Finishes			
Finishes Available	MD-AC370	Satin Finish Art Canvas	

Roll Presentation	
Roll Widths Roll Lengths	0.76m / 1.37m / 1.60m 15m
Durability	
Shelf Life	Long term (10-20°C and 50% R.H). Store
External weathering	Long term indoor and short term
	outdoor. Water fast.
Fire Rating	Self-extinguishing.
Regulations	REACH & RoHS compliant

### **Printing and Handling**

- Ensure that the material has reached recommended room temperature and a relative humidity before printing.
- Do not handle the face film directly and ensure it is free from dust and static.
- When stretching the canvas over a frame it is recommended to use a frame with a very slightly bevelled edge which will avoid any possible minor cracking.
- Suitable for use on Solvent and Eco Solvent inkjet printers, as well as UV Curable and HP Latex. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- Allow 24 hours after printing for the ink to gain full abrasion resistance. Do not stack prints until fully cured.
- The product is designed to be used without an overlaminate. If a liquid laminate is used it is the responsibility of the user to test.
- The durability of the finished print is dependent on the inks and printer.



#### MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Media and Overlaminates will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Media and Overlaminates becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.