

Metamark MD-RU330

Layflat Roll Up - 330gsm



Product Description

MD-RU330 is semi-rigid print media, for use on roller banner cassette display systems, and other POS, retail and exhibition applications. The product offers excellent layflat properties and printer compatibility including Latex. It has a smooth matt white finish providing vibrant graphics, a grey 'lightstop' backing and is to be used without overlamination.

Features & Benefits

- 330gsm PVC/PET film
- Printable with Solvent, Eco Solvent, UV and Latex inks
- Grey backing to provide high levels of opacity
- Scratch resistant without lamination

Face Film		Roll Presentation	
Type	PVC/PET, grey lightstop backing	Roll Widths	0.914m / 1.07m / 1.37m
Weight	330gsm	Roll Lengths	10m / 50m
Tensile strength	1182 / 1173 N/5cm (warp / weft)	Presentation	Face film outwards
Tear Strength	34 / 27 N/5cm (warp / weft)		

Finishes			Durability	
Finish Available	MD-RU330	Matt Textured	Shelf Life	2 years
			Durability	Indoor use, waterproof.
			Fire Rating	Self-extinguishing. The fire rating is a function of the substrate.
			Regulations	REACH compliant

Handling and Printing

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- The product is designed to be used without overlaminating. It may also be overlaminated with MetaGuard 302.
- Do not stack prints until fully cured. If a take up roller is used then a silicon liner may be interleaved to prevent blocking.
- Allow the inks to cure before use, this is nominally 24-48 hours but dependant on the inks.
- The durability of the finished print is dependent on the inks and printer.

MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Media and Overlaminates will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Media and Overlaminates becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

☐ Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147
☐ Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax =44 (0)1483 570540

sales@metamark.co.uk
www.metamark.co.uk