Metamark MD-TX3

WallTex Self-Adhesive Textile Wall Media



Product Description

Metamark 'WallTex' is a self-adhesive Polyester fabric, offering a clean, easy to apply alternative to traditional wall coverings. The fabric with its lightly textured weave is PVC free, and ideal for visual merchandising, exhibition and home décor applications. The repositionable adhesive is removable in the short term on sealed surfaces, allowing clean easy to replace wall décor coverings. It produces outstanding print results on Solvent, Eco Solvent, Latex and UV printers. Environmentally safe and bio-degradable over time, MD-TX3 is both PVC free and non-toxic

Features & Benefits

- PVC, VOC and Heavy metal free.
- Solvent adhesive and PE Liner.

- Clean removable, residue free adhesive.
- For Solvent, Eco Solvent, Latex and UV printing.

Fabric Specif				
abric Finish	100% polyester Woven fabric Soft Sheen	Finishes Available	MD-TX3	White
/eight 245gsm		Roll Presentation		
Denier	150Dx150D	Roll Widths	1.37m	
hickness	190 mic	Roll Lengths	30m	
Opacity	95%	Durability		
Adhesive		Shelf Life	1 years. (10-20°C and 50% R.H). Indoor use only	
ӯре	Grey blockout, Solvent-based Acrylic	External weathering Fire Retardant		
Release Liner		Regulations	B2 REACH Compliant.	
rint	Plain	5	·	
Veight	100 gsm nominal			
ӯре	Kraft with PE coating			
Printing and H	landling	Ensure the surface is a	lean from contamir	nation, dust free, and
Always perform a test print first. Ensure that the correct profiles		dry before applying graphics.		
and heater settings are used. Refer to www.metamark.co.uk.		 Apply using a dry application method. 		
 Ensure that the material has reached room temperature and a subsidiary in a figure of some station 		 Testing for suitability is recommended prior to applications. 		
relative humidity of 50% before printing. Do not handle the face film, ensure free from dust and static.		 Edges and overlaps should be applied with heat and a roller. 		
Do not handle the face him, ensure free from dust and static.		Notes		
Application		 Due to the variability of walls it is vital to assess the suitability, and 		
• Allow a minimum of 24-48 hours for the solvents to dry off before		 surface preparation needed. It is suitable for smooth walls. No liability is given for damage to painted surfaces as the bond between the paint and the wall is out of our control. 		
application, depending on the print and drying conditions this can often be in excess of 48 hours. Retained solvents will reduce				

MetaSure® Warranty

PVC Free

This product contains no plasticisers, phthalates or chlorine.

Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Media and Overlaminates will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Media and Overlaminates becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. The above data is given in good faith to provide an indication of the performance of the product. Purchaser should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited