

R Tape Apli Tape

Standard High Tack Paper Application Tape



Product Description

A standard high tack paper application tape, R Tape Apli Tape® is a high quality product suited to general sign applications. R Tape's products have long been recognized as the leading application tapes in the sign industry. It is designed to work well with a wet application method, with no stringing of the adhesive, and provides a clean tear for fast workability. R Tape Apli Tape is supplied in 1220mm x 91.4m rolls.

Features

- Standard High Tack Tape for general sign applications
- High quality for complete consistency.
- Clean tear for fast working.
- No stringing of adhesive.
- Excellent for 'wet application work'*

Application

- Apply firm pressure with a squeegee.
- Graphics are best removed with the application tape facing downwards and lifting the release liner upwards.
- If the tape becomes wet, remove immediately after application while still wet, to prevent leaving residue on the vinyl.

Storage

- Store in a cool, dry place. The paper and rubber based adhesive absorb moisture over time which will cause it to 'block' onto the roll if not stored correctly. This can also be prevented by storing in the polythene bag. Do not leave exposed in cold or damp conditions for any period of time. Do not get wet. Store on end.

Type		Specifications	
Adhesive:	Natural rubber	Tape thickness:	102-115 mic
Tack:	Standard High Tack	Tensile Strength:	74 N/25mm PSTC 31
Paper:	Special white	Adhesion:	17-19.7 N/100mm
Roll Sizes	1220mm x 91.4m	Elongation:	3-4%

Warranty: Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

○ Lunesside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147

○ Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540

sales@metamark.co.uk
www.metamark.co.uk