Metamark MD-PU2

Textured Lightstop for 'Pop Up' Displays – 385 micron



Product Description

Metamark MD-PU2 is a 385 micron, semi rigid, 'Pop up' polyester, for use on solvent, Latex & UV inkjet printers. It has a bright white textured printable surface that is scratch resistant and an antistatic treatment that avoids attracting dust. The premium 'Pop up' material has a grey back offering 98% opacity. For use with modular 'Pop Up' display systems, for use in exhibitions and for POS. One part system for use without overlamination.

Features & Benefits

- 385 micron Polyester film.
- Printable with Solvent, Eco Solvent, UV and Latex inks
- Grey backing to provide high levels of opacity.
- PVC, Phthalate and Chlorine Free.
- Scratch resistant textured surface.
- One Part System, no need for lamination.

Face Film			Roll Presentation	
Type Thickness Weight	Polyester Film, grey lightstop backing 385 micron 540gsm		Roll Widths Roll Lengths Presentation	0.914m / 1.27m 20m Face film outwards
Finishes			Durability	
Finish Available	MD-PU2	Bright White	Shelf Life Durability Fire Rating	1 years Indoor use, waterproof. Combustible but not readily ignited

Handling and Printing

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- The product is designed to be used without overlaminating.
- Do not stack prints until fully cured. If a take up roller is used then a silicon liner may be interleaved to prevent blocking.
- Allow the inks to cure before use, this is nominally 24-48 hours but dependant on the inks.
- The durability of the finished print is dependent on the inks and printer.



This product contains no plasticisers phthalates or chlorine.

MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Media and Overlaminates will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Media and Overlaminates becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. The above data is given in good faith to provide an indication of the performance of the product. Purchaser should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited